



# BMK SERIES

## TECHNICAL DATA SHEET

### Benchmark 750 - 6000

#### Condensing Hydronic Boilers




The AERCO Benchmark (BMK) Water Boiler is designed for condensing application in any closed loop hydronic system. It delivers unmatched burner modulation to match energy input directly to fluctuating system loads to yield the highest possible seasonal efficiencies. And no other product packs as much capacity into such a small footprint.

To minimize emissions, the BMK Series is fitted with a low NOx burner whose emissions will meet the most stringent NOx and CO requirements. The fully modulating burner also maintains AERCO standards for energy efficiency, longevity, reliability and construction quality.

The BMK Series comes standard with AERCO's Patent Pending, Oxygen Level (O<sub>2</sub>) monitoring system. This monitoring system, designed to display the O<sub>2</sub> level directly on the unit in real time, can also be remotely monitored via Modbus giving the customer the ability to measure the emissions level and fuel economy of the boiler without traditional combustion calibration devices.

The BMK boilers can be used as an individual unit or in modular arrangements and offers selectable modes of operation. In addition to controlling the boiler according to a constant set point, indoor/outdoor reset schedule or 4-20mA signal, one or more units can be integrated via Modbus communications protocol. For boiler plants ranging from 2-8 boilers, AERCO'S built-in Boiler Sequencing Technology (BST)\* can be utilized. For heating plants greater than 8 boilers, AERCO's ACS (AERCO Control System) provides the right solution. Likewise, Benchmark systems can be easily integrated with a facility-wide Energy Management or Building Automation System.



## FEATURES:

- Natural Gas, Propane, or Dual Fuel (model dependant)
- 20:1 Turndown Ratio (5%) depending on capacity
- Oxygen Level (O<sub>2</sub>) Monitoring Standard
- Stainless Steel Fire Tube heat exchanger
- Capable of variable primary flow Installations
- NOx Emissions capable of 9PPM or less @ all firing rates \*depending on capacity
- Compact Footprint
- Precise Temperature Control
- On-board Boiler Sequencing Technology (BST)
- Ducted Combustion Air Capable
- Easy Open Access for Service
- Acceptable vent materials AL29-4C, Polypropylene, PVC, cPVC (model dependant)
- Reliable Quiet Operation
- Controls Options
  - Constant Setpoint
  - Indoor/ Outdoor Reset
  - Remote Setpoint
  - 4-20mA signal or ModBus


## RATINGS:

Model Number	Min Input MBH	Max Input MBH	Max Output <sup>a</sup> MBH	Efficiency Range	AHRI Efficiency 80° to 180°F
<b>BMK 750</b>	50	750	653-720	87%-98%	95.50%
<b>BMK 1000</b>	50	1000	870-960	87%-98%	96.80%
<b>BMK 1500</b>	75	1500	1305-1425	87%-98%	94.60%
<b>BMK 2000</b>	100	2000	1740-1900	87%-98%	94.60%
<b>BMK 2500</b>	167	2500	2175-2360	87%-98%	93.50%
<b>BMK 3000</b>	200	3000	2610-2880	87%-98%	93.50%
<b>BMK 6000**</b>	400	6000	5220-5670	87%-98%	94.50%

<sup>a</sup>Max output dependent upon application - See efficiency curves

\*\*See separate BMK6000 Technical Data Sheet for additional BMK6000 details

## DIMENSIONS (INCHES):



Model	(Width) A	(Depth) B	(Height) C	D	E	F	G	H	I	J	K	L
<b>BMK 750</b>	28"	25"	78"	34"	10"	10"	53"	21"	17"	4"	5"	51.8"
<b>BMK 1000</b>	28"	25"	78"	34"	10"	10"	53"	21"	17"	4"	5"	51.8"
<b>BMK 1500</b>	28"	43.6"	78"	58.4"	7"	11.5"	57.8"	18"	22"	8.9"	4.7"	19.5"
<b>BMK 2000</b>	28"	43.6"	78"	58.4"	7"	11.5"	57.8"	18"	22"	8.9"	4.7"	19.5"
<b>BMK 2500</b>	28"	56"	78"	68.4"	5.4"	11.5"	57.8"	18"	22"	6.4"	3.6"	26"
<b>BMK 3000</b>	28"	56"	78"	68.4"	5.4"	11.5"	57.8"	18"	22"	6.4"	3.6"	26"
<b>BMK 6000**</b>	34"	89.3"	79.4"	108.3"	6.2"	42.1"	N/A	15.6"	N/A	10"	28.7"	23.7"

\*\*See separate BMK6000 Technical Data Sheet for additional BMK6000 dimension details

\*\*\*BMK750/1000 Feature Dual Inlet Connections

## SPECIFICATIONS:

	BMK750	BMK1000	BMK1500	BMK2000	BMK2500	BMK3000	BMK 6000**
Boiler Category	ASME Sect.IV	ASME Sect.IV	ASME Sect.IV	ASME Sect.IV	ASME Sect.IV	ASME Sect.IV	ASME Sect.IV
Gas Connections (NPT)	1"	1"	2"	2"	2"	2"	2"
Max. Gas Pressure	14"	14"	14"	14"	14"	14"	2psi
Min. Gas Pressure <sup>1</sup>	4"	4"	4"	4"	4"	4"	14"
Max. Allowed Working Pressure	160 PSIG	160 PSIG	160 PSIG	160 PSIG	160 PSIG	160 PSIG	80 PSIG/150 PSIG Optional
Electrical Req. 120V/1PH/60Hz <sup>2</sup>	13 FLA	13 FLA	16 FLA	16 FLA	N/A	N/A	N/A
Electrical Req. 208V/3PH/60Hz <sup>2</sup>	N/A	N/A	N/A	N/A	10 FLA	10 FLA	19 FLA
Electrical Req. 460V/3PH/60Hz <sup>2</sup>	N/A	N/A	N/A	N/A	5 FLA	5 FLA	12 FLA
Water Connections (Flanged)	3"	3"	4"	4"	4"	4"	6"
Min. Water Flow (GPM)	25	25	25	25	25	25	75
Max. Water Flow (GPM)	175	175	250	350	350	350	600
Water Volume Gallons	16.25	14.25	44	40	58	55	110
Water Pressure Drop	3.0 PSIG @ 100 GPM	3.0 PSIG @ 100 GPM	3.0 PSIG @ 170 GPM	3.0 PSIG @ 170 GPM	3.0 PSIG @ 218 GPM	3.0 PSIG @ 261 GPM	4.0 PSIG @ 500 GPM
Turndown	15:1 (7%)	20:1 (5%)	20:1 (5%)	20:1 (5%)	15:1 (7%)	15:1 (7%)	15:1 (7%)
Vent/Air Intake Connections	6 Inch	6 Inch	6 Inch	8 Inch	8 Inch	8 Inch	14 Inch
Vent Materials	AL29-4C Polypro, CPVC, PVC	AL29-4C Polypro, CPVC, PVC	AL29-4C Polypro	AL29-4C Polypro	AL29-4C Polypro	AL29-4C Polypro	AL29-4C
Type of Gas	Natural Gas, Propane	Natural Gas, Propane	Natural Gas, Propane, Dual Fuel	Natural Gas, Propane, Dual Fuel	Natural Gas, Propane, Dual Fuel	Natural Gas, Propane, Dual Fuel	Natural Gas, Dual Fuel
NOx Emissions <9ppm Capability*	✓	✓	✓	✓	N/A (<20 ppm)	N/A (<20ppm)	✓
Temperature Control Range	50°F to 190°F						
Ambient Temperature Range	0°F to 130°F						
Standard Listings & Approvals	UL, CUL, CSD-1, ASME, AHRI						
Gas Train Operations	FM Compliant or Factory Installed DBB (IRI) (BMK750-BMK3000 Only) FM Compliant (BMK 6000)						
Weight (dry) lbs.	669	700	1406	1500	2,000	2,170	3,000
Weight (wet) lbs.	802	817	1654	1760	2,332	2,580	3,920
Shipping Weight lbs.	862	900	1606	1700	2,200	2,370	3,800

\*\*See separate BMK6000 Technical Data Sheet for additional BMK6000 details

<sup>1</sup> Values are for Natural Gas FM Compliant gas trains only. See Benchmark Gas Components & Supply Design Guide GF-2030 for Propane, DBB & Dual Fuel gas train minimum gas pressure requirements.

<sup>2</sup> See Benchmark Electrical Power Guide GF-2060 for Service Disconnect Switch amperage requirements.

**NOTES:**

**Represented By:**

Specifications subject to change without prior notice. Consult website or contact AERCO.  
BMK SERIES 03/2014 NY



WATER HEATERS • BOILERS • PARTS & ACCESSORIES  
AERCO INTERNATIONAL, INC.  
100 ORITANI DR. • BLAUVELT, NY 10913  
(845) 580-8000 • FAX (845) 580-8090  
[www.aerco.com](http://www.aerco.com)